

维控 130 系列伺服电机参数见下表

类别	伺服电机型号	电源	法兰	额定功率 (kW)	额定扭矩 (N.m)	额定转速 (rpm)	额定电流 (A)	最大扭矩 (N.m)
VD 系列	WD40M-01030S○☆	220V 供电	40	0.1	0.32	3000	1	0.95
	WD60M-02030S○☆		60	0.2	0.64	3000	1.7	1.92
	WD60M-04030S○☆			0.4	1.27	3000	2.5	3.81
	WD80M-07530S○☆		80	0.75	2.39	3000	4.4	7.17
VE 系列	WE60M-04030S○☆		60	0.4	1.27	3000	2.6	3.8
	WE80M-07320S○☆		80	0.73	3.5	2000	3	10.5
	WE80M-07530S○☆			0.75	2.39	3000	3	7.1
	WE80M-10025S○☆			1	4	2500	4.4	12
	WE80M-11030S○☆			1.1	3.5	3000	4	10.5
	WE80M-12030S○☆			1.2	4	3000	4.5	12
	WE110M-06030S○☆			110	0.6	2	3000	2.5
	WE110M-08020S○☆		0.8		4	2000	3.5	12
	WE110M-12030S○☆		1.2		4	3000	5	12
	WE110M-12020S○☆	1.2	6		2000	4.5	12	
	WE110M-15030S○☆	1.5	5		3000	6	15	
	WE110M-18030S○☆	1.8	6		3000	6	18	
	WE110M-18030S○☆	130	1	4	2500	4	12	
	WE130M-10010S○☆		1	10	1000	4.5	20	
	WE130M-13025S○☆		1.3	5	2500	5	15	
WE130M-15025S○	1.5		6	2500	6	18		

☆								
WE130M-15015S○ ☆			1.5	10	1500	6	25	
WE130M-20025S○ ☆			2	7.7	2500	7.5	22	
WE130M-23015S○ ☆			2.3	15	1500	9.5	30	
WE130M-26025S○ ☆			2.6	10	2500	10	25	
WE130M-38025S○ ☆			3.8	15	2500	13.5	30	
WE130M-20025T○ ☆			2	7.7	2500	6	18	
WE130M-26025T○ ☆			2.6	10	2500	6	25	
WE130M-38025T○ ☆		130	3.8	15	2500	7.5	22	
WE130M-42020T○ ☆			4.2	20	2000	8.5	60	
WE130M-53030T○ ☆			5.3	17	3000	9.5	30	
WE180M-30015T○ ☆	380V 供电		3	19	1500	10	25	
WE180M-43015T○ ☆		180	4.3	27	1500	13.5	30	
WE180M-45020T○ ☆			4.5	21.5	2000	9.5	53	
WE180M-55015T○ ☆			5.5	35	1500	13.5	30	

○：A1-17bit 单圈磁编；C1-17bit 多圈磁编；D2-23bit 多圈光编。

☆：F-油封；G-油封带抱闸。

注 1：以上电机选型参数仅供参考

注 2：配置 2500 线增量式光编的电机型号，请联系维控业务员。