

Model	V-Net Functions								MQTT	Lua Script	LAN Monitoring	4G / WIFI
	Realtime Data	Alarm Data	History Data	APP & Remote Control	Remote Update HMI	WVPN	Cloud SCADA	Pass-through				
PI3070ig	X	X	X	✓	✓	✓	X	Serial	✓	✓	✓	X
PI3070ig (G)	X	X	X	✓	✓	✓	X	Serial	✓	✓	✓	4G
PI3070ig (AG)	X	X	X	✓	✓	✓	X	Serial	✓	✓	✓	4G(global)
PI3070ig (W)	X	X	X	✓	✓	✓	X	Serial	✓	✓	✓	WIFI
PI3070ig-C	100	20	50	✓	✓	✓	✓	Serial	✓	✓	✓	X
PI3070ig-C(G)	100	20	50	✓	✓	✓	✓	Serial	✓	✓	✓	4G
PI3070ig-C(AG)	100	20	50	✓	✓	✓	✓	Serial	✓	✓	✓	4G(global)
PI3070ig-C(W)	100	20	50	✓	✓	✓	✓	Serial	✓	✓	✓	WIFI
PI3070ig-CH(W)*	100	20	50	✓	✓	✓	✓	Serial	✓	✓	✓	WIFI
PI3070ig-CH(G)*	100	20	50	✓	✓	✓	✓	Serial	✓	✓	✓	4G
PI3102ig-CH(AG)*	100	20	50	✓	✓	✓	✓	Serial	✓	✓	✓	4G(global)
PI3070ig-O	X	X	X	X	X	X	X	X	X	✓	✓	X

Notes: * The resolution is 1024*600

SPECIFICATIONS

Main Display	Processor	High Performance CPU	
	Size	7"	
	Screen	TFT	
	Resolution	800*480	
	Brightness (cd/m2)	250	
	Backlight	LED	
	Backlight Lifetime	50,000 hours	
	Touch Panel	High precision four-wire resistive	
	Storage	Memory	128 MB
		Flash	128 MB
SD Card Slot		YES	
USB Port		USB2.0 Host + USB2.0 Client (Could not use at the same time)	
RTC	Real-time clock	Yes	
	Calendar	Yes	
I/O Port	COM1	CN1:RS422/RS485 CN2:RS232 CN3:RS485	
	COM2	--	
	COM3	--	
	Ethernet	x1	
	CANopen	--	
	Power	Rated Power	< 8W
		Power Voltage	DC 24V
Input range		DC 12 ~ 28V	
Shell Color		Grey	
Enclosure	Shell Material	Plastic+ABS(Polycarbonate)	
	Overall Size (mm)	201.2W*147.2H*39.0D	
	Mounting Size (mm)	192.0W*138.0H	
	Mounting Method	Panel Mount	
	Weight (Kg)	0.52	
Environment	Working Temperature	-10 ~ 55°C	
	Storage Temperature	-20 ~ 70°C	
	Humidity	10 ~ 90%RH (Non-condensing)	
	Vibration Resistance	10 ~ 25 Hz (X, Y, Z direction 2G/30 minutes)	
	Cooling	Air Cooling	
Software	Programming	PI Studio	
	Remote Access	YES	
	Email Alarm	YES	
	IP Camera	--	
	Audio Output	--	
	Video Player	--	
	Data Tool	Yes	
Certificates	IP Code	IP65 (Front panel)	
	CE	CE Marked	
	FCC	FCC Class A	

