

Model	KW	HP	Rated input current(A)	Rated output current(A)	Input Voltage	General type / Fan type	Integrated with brake function
VB-4T132G/4T160P	132 / 160	180 / 220	256 / 307	253 / 304	380~440V / Three phase	General type / Fan type	N/A
VB-4T160G/4T185P	160 / 185	220 / 255	307 / 345	304 / 340	380~440V / Three phase	General type / Fan type	N/A
VB-4T185G/4T200P	185 / 200	255 / 275	345 / 385	340 / 377	380~440V / Three phase	General type / Fan type	N/A

Specification

Control characteristic	Control mode	V/F Control; Sensorless Vector Control (SVC); Torque Control
	Starting torque	G Type: 0.5Hz/150 % (SVC); P Type: 0.5Hz/100%
	Speed adjustment range	1:100 (SVC)
	Speed holding precision	± 0.5 % (SVC)
	Overload capability	G Type: 150 % rated current for 60s; 180 % rated current for 1s P Type: 120 % rated current for 60s; 150 % rated current for 1s
Input / Output	Input voltage	380V/415V/440V; fluctuation range: 380V(-15%)~440V(+10%)
	Input frequency	50/60Hz, fluctuation range: ±5%
	Output voltage	0-rated input voltage
	Output frequency	SVC: 0~320Hz, V/F: 0~1000Hz
	Analog input	2 channels
Input / Output terminals	Digital input	6 channels
	Analog output	2 channels
	Digital output	1 channel
	Relay output	2 channels
	RS485 communication terminal	1 channel
Application environment	Power supply	2 channels (1 channel 10V, 1 channel 24V)
	Attitude	Lower than 1000m, service is derated capability above 1000m, derate 1% capacity every 100m increased in height.
	Environment temperature	-10°C ~ + 40°C (service is derated capability for 40°C ~ 50°C)
	Humidity	<95%RH, no water condensation
	Vibration	< 5.9m/s ² (0.6g)
Enclosure	Storage temperature	-40°C~+ 60°C
	Shell Material	Metal
	Overall Size (mm)	869.00H*502.00W*355.00D
	Weight (Kg)	89
	Package dimensions (mm)	985.00H*610.00W*540.00D

