

Model	V-Net Functions								MQTT	Lua Script	LAN Monitoring	4G / WIFI
	Realtime Data	Alarm Data	History Data	APP & Remote Control	Remote Update HMI	WVPN	Cloud SCADA	Pass-through				
PI3043ig-C	100	20	50	✓	✓	✓	✓	Serial	✓	✓	✓	X

SPECIFICATIONS

Main Display	Processor	High Performance CPU
	Size	4.3"
	Resolution	480*272
	Brightness (cd/m2)	300
	Backlight	LED
Storage	Backlight Lifetime	50,000 hours
	Touch Panel	High precision four-wire resistive
	Memory	128MB
	Flash	128MB
	SD Card Slot	--
RTC	USB Port	USB2.0 Host or USB2.0 Type-C (Can not use at the same time)
	Real-time clock	Yes
I/O Port	Calendar	Yes
	COM1	CN1:RS422/RS485 CN2:RS232 CN3:RS485
	COM2	--
	COM3	--
	Ethernet	x1
Power	CANopen	--
	Rated Power	< 8W
	Power Voltage	DC 24V
Enclosure	Input range	DC 12 ~ 28V
	Shell Color	Grey
	Shell Material	Plastic+ABS(Polycarbonate)
	Overall Size (mm)	142.0W*86.0H*30.5D
	Mounting Size (mm)	131.0W*78.0H
Environment	Mounting Method	Panel Mount
	Weight (Kg)	0.39
	Working Temperature	-10 ~ 55°C
	Storage Temperature	-20 ~ 70°C
	Humidity	10 ~ 90% RH (Non-condensing)
Software	Vibration Resistance	10 ~ 25 Hz (X, Y, Z direction 2G/30 minutes)
	Cooling	Air Cooling
	Programming	PI Studio
	Remote Access	YES
	Email Alarm	YES
Certificates	IP Camera	N/A
	Audio Output	--
	Video Player	--
	Data Tool	Yes
	IP Code	IP65 (Front panel)
	CE	CE Marked
	FCC	FCC Class A



Unit : mm , error range: ±0.5mm

